



FITTING INSTRUCTIONS FOR JENKS' TRIUMPH SEAT COWL "THUMB BOLTS"

Application

Our Triumph Seat Cowl Bolts, TCN 02 are designed to replace the Allen headed bolt used by Triumph to hold the rear seat cowl to the Triumph Thruxton 900 and Daytona 995i.

Our Cowl Bolts are based on the proven Jenks "Thumb Bolt", originally developed to replace the Allen bolts used to secure the Bonneville and Thunderbird seat and side covers.

Our new very compact Seat Cowl Bolts make removing and replacing the seat cowl a 1 minute tool free job!

The bolts are machined from billet aluminum and then finished with bright nickel plate, to protect the aluminum and give years of trouble free use. Each bolt has a blind leading end to make positive location easy and minimize the risk of a crossed thread.



Installation

Using the Triumph supplied Allen key remove the two bolts. Fit the two new Jenks Thumb bolts and tighten to 20Nm, which is about as tight as can be made using fingers on the knurled grip. Do not tighten with pliers.

IMPORTANT:

- Before riding always check the Thumb Bolts are tight.
- Do not attach bungee cords to the Thumb Bolts: they are NOT designed for this purpose.

Made in England by:

The Jenks Partnership Limited,
PO Box 1840, Salisbury, Wiltshire SP5 3AW,
United Kingdom

Phone: +44 1722 711 745
e-mail: info@triumph-bonneville.com

Issue Z: June 2004

© The Jenks Partnership Ltd 2004.

"Jenks Bolts" and the "tJP Logo" are Registered Trade Marks of The Jenks Partnership Limited.